2025/09/07 18:18 1/3 Unattended Updates

# **Unattended Updates**

In order to install updates automatically, the unattended-upgrades package needs to be installed and configured. It can install only security updates or updates from any branch or repository that's desired. It can reboot automatically or not at all and it can exclude specific packages.

#### Initial installation and configuration

```
apt-get install unattended-upgrades
```

```
vi /etc/apt/apt.conf.d/50unattended-upgrades
#uncomment the desired origin. For only security updates, comment out
everything else
Unattended-Upgrade::Origins-Pattern {
      "o=Debian, n=stretch";
      "o=Debian, n=stretch-updates";
      "o=Debian, n=stretch-proposed-updates";
      "o=Debian, n=stretch, l=Debian-Security";
//To enable ALL updates, use this:
        "site=*":
//
};
#blacklist packages as required (mysql-server,mysql-client,apache,php etc)
Unattended-Upgrade::Package-Blacklist {
    "mysql-server*";
    "mysql-common*";
    "default-mysql-server";
    "php7.0-*";
    "apache2*";
    "blink";
    "python-sipsimple";
};
#Don't force updates
Unattended-Upgrade::AutoFixInterruptedDpkg "false";
#set mail to whoever should receive it and make sure bsd-mailx or sendmail
#is installed and able to send mails
Unattended-Upgrade::Mail "root";
#configure reboot if desired.
Unattended-Upgrade::Automatic-Reboot "false";
```

to enable the automatic updates:

```
vi /etc/apt/apt.conf.d/20auto-upgrades
```

```
APT::Periodic::Update-Package-Lists "1";
APT::Periodic::Download-Upgradeable-Packages "1";
APT::Periodic::AutocleanInterval "3";
APT::Periodic::Unattended-Upgrade "1";
```

To increase the frequency from daily to every 4 hours, this can be entered into cron.d. This will override the time period configured in /etc/apt/apt.conf.d (note, in Ubuntu systems the timer daily cron timer is triggered via the systemd apt-daily.timer:

```
vi /etc/cron.d/unattended-upgrade
0 */4 * * * root sleep $(( 1$(date +\%N) \% 14400
));PATH=/usr/local/sbin:/usr/local/bin:/sbin:/usr/sbin:/usr/bin
unattended-upgrade
```

Test the configuration using:

```
sudo unattended-upgrades --dry-run
tail /var/log/unattended-upgrades/unattended-upgrades.log
```

#### **Additional Repositories**

To include additional repositories, the origin and suite (archive) names need to be identified first:

```
grep "Origin:" /var/lib/apt/lists/*Release
/var/lib/apt/lists/gb.archive.ubuntu.com ubuntu dists bionic-
backports InRelease:Origin: Ubuntu
/var/lib/apt/lists/gb.archive.ubuntu.com ubuntu dists bionic InRelease:Origi
n: Ubuntu
/var/lib/apt/lists/gb.archive.ubuntu.com ubuntu dists bionic-
updates InRelease:Origin: Ubuntu
/var/lib/apt/lists/ppa.launchpad.net team-xbmc xbmc-
nightly ubuntu dists bionic InRelease:Origin: LP-PPA-team-xbmc-xbmc-nightly
/var/lib/apt/lists/security.ubuntu.com ubuntu dists bionic-
security InRelease:Origin: Ubuntu
grep "Suite:" /var/lib/apt/lists/*Release
/var/lib/apt/lists/gb.archive.ubuntu.com_ubuntu_dists_bionic-
backports InRelease:Suite: bionic-backports
/var/lib/apt/lists/gb.archive.ubuntu.com ubuntu dists bionic InRelease:Suite
: bionic
/var/lib/apt/lists/qb.archive.ubuntu.com ubuntu dists bionic-
updates InRelease:Suite: bionic-updates
/var/lib/apt/lists/ppa.launchpad.net team-xbmc xbmc-
nightly ubuntu dists bionic InRelease:Suite: bionic
/var/lib/apt/lists/security.ubuntu.com ubuntu dists bionic-
security InRelease: Suite: bionic-security
```

These details are needed to edit the 50unattended-upgrades file and add the lines using this format

http://wuff.dyndns.org/ Printed on 2025/09/07 18:18

2025/09/07 18:18 3/3 Unattended Updates

"<origin>:<archive>"; of for this examples sake "Google\, Inc.:stable";. Example for Kodi on ubuntu:

```
//Kodi Nightly
"LP-PPA-team-xbmc-xbmc-nightly:${distro_codename}";
```

## Notify required reboot on login

```
vi /root/.profile
```

add after the .bashrc call, but before the mesg line:

```
[ -f /var/run/reboot-required ] && echo -e "\n*** System restart required
***\n"
```

### Running on battery

For unattended-upgrades to skip upgrades when the system is running on battery, the following package needs to be installed:

apt-get install powermgmt-base

From:

http://wuff.dyndns.org/ - Wulf's Various Things

Permanent link:

http://wuff.dyndns.org/doku.php?id=linux:unattended-updates&rev=1685357734



