

# Docker PHP Dev

<https://github.com/TrafeX/docker-php-nginx>

PHP,nginx,mariadb combo docker compose file with default innodb (155mb base conf dir size):

[docker-compose.yml](#)

```
services:
  php-dev:
    image: trafex/php-nginx
    container_name: php-dev
    restart: unless-stopped
    environment:
      - PUID=1016
      - PGID=1016
      - TZ=Europe/London
    ports:
      - 7082:8080
    volumes:
      - /opt/php-dev/html:/var/www/html
      #- /opt/php-dev/php-conf/php.ini:/etc/php84/conf.d/settings.ini
      #- /opt/php-dev/php-conf/php-fpm.conf:/etc/php84/php-fpm.d/server.conf
    depends_on:
      - php-dev-mysql
    # docker exec php-dev bash
    stdin_open: true # docker run -i
    tty: true # docker run -t
  networks:
    - php-dev-network
  php-dev-mysql:
    image: yobasystems/alpine-mariadb
    container_name: php-dev-mysql
    environment:
      MYSQL_ROOT_PASSWORD: devroot
      MYSQL_DATABASE: dev
      MYSQL_USER: dev_user
      MYSQL_PASSWORD: dev_pass
      MYSQL_CHARSET: utf8
      MYSQL_COLLATION: utf8_general_ci
    expose:
      - "3306"
    ports:
      - 23306:3306/tcp
    volumes:
      - /opt/php-dev/mysql-data:/var/lib/mysql
      #- /opt/php-dev/mysql-logs:/var/lib/mysql/mysql-bin
      #- /opt/php-dev/mysql-conf/my.cnf:/etc/my.cnf
```

```

# - /opt/php-dev/mysql-conf/mariadb-
server.cnf:/etc/my.cnf.d/mariadb-server.cnf
# - /opt/php-dev/mysql-conf/00_aria.cnf:/etc/my.cnf.d/00_aria.cnf
restart: unless-stopped
networks:
- php-dev-network
# docker exec php-dev-mysql mysql -uroot -pdevroot dev
stdin_open: true
tty: true

networks:
php-dev-network:

```

To use aria (myisam based) by default, enable 00\_aria.cnf volume and create this file:

[/opt/php-dev/mysql-conf/00\\_aria.cnf](/opt/php-dev/mysql-conf/00_aria.cnf)

```

[mysqld]
skip-innodb
default-storage-engine=Aria
default-temp-storage-engine=Aria
innodb=OFF
symbolic-links=0
log-output=file
skip-host-cache
skip-name-resolve

```

## self-build for other php exts

Adjustments/self build of the php container to add or remove php extensions when necessary:

<git clone https://github.com/TrafeX/docker-php-nginx>

<docker-compose.yml>

```

services:
php-dev:
image: php-dev:latest
build:
context: .
no_cache: true
container_name: php-dev
restart: unless-stopped
environment:
- PUID=1016

```

```
- PGID=1016
- TZ=Europe/London
ports:
- 7081:8080
volumes:
- /opt/php-dev/html:/var/www/html
#- /opt/php-dev/conf/php.ini:/etc/php84/conf.d/settings.ini
#- /opt/php-dev/conf/php-fpm.conf:/etc/php84/php-
fpm.d/server.conf
```

Create custom php.ini if required:

#### [config/php.ini](#)

```
[PHP]
allow_url_fopen=On

max_execution_time = 600

[Date]
date.timezone="UTC"
expose_php= Off
```

Adjust Dockerfile to add/remove any extensions as required. E.g.:

```
RUN apk add --no-cache \
curl \
nginx \
php84 \
php84-ctype \
php84-curl \
php84-dom \
php84-fileinfo \
php84-fpm \
php84-intl \
php84-mbstring \
php84-opcache \
php84-phar \
php84-session \
php84-tokenizer \
php84-xml \
php84-xmlreader \
php84-xmlwriter \
php84-sqlite3 \
php84-mysqli \
supervisor
```

Add mysql docker if required:

```
name: php-dev-mysql
services:
  energystats2-mysql:
    image: yobasystems/alpine-mariadb
    container_name: php-dev-mysql
    environment:
      MYSQL_ROOT_PASSWORD: rootpassword
      MYSQL_DATABASE: database
      MYSQL_USER: username
      MYSQL_PASSWORD: password
      MYSQL_CHARSET: utf8
      MYSQL_COLLATION: utf8_general_ci
    expose:
      - "3306"
    ports:
      - 13306:3306/tcp
    volumes:
      - /opt/php-dev-mysql-storage/data:/var/lib/mysql
      # - /opt/php-dev-mysql-storage/logs:/var/lib/mysql/mysql-bin
      - /opt/php-dev-mysql-storage/conf/my.cnf:/etc/my.cnf
      # - /opt/php-dev-mysql-storage/conf/mariadb-
server.cnf:/etc/my.cnf.d/mariadb-server.cnf
```

From:

<http://wuff.dyndns.org/> - **Wulf's Various Things**



Permanent link:

<http://wuff.dyndns.org/doku.php?id=php:docker-php-dev>

Last update: **2025/05/04 01:31**