

Docker

<https://docs.docker.com/storage/volumes/>

Update docker container to latest version via docker compose:

```
#Single container:
docker compose pull calibre-web
docker compose up -d calibre-web
docker image prune

#Update all containers:
docker compose pull
docker compose up -d
docker image prune
```

Docker compose health checks:

<https://medium.com/geekculture/how-to-successfully-implement-a-healthcheck-in-docker-compose-efced60bc08e>

Copying files from/to images

```
docker cp dockerimage:/bla ./bla
docker cp ./bla dockerimage:/bla
```

Change mount points of existing docker containers;

e.g. mount /home/<user-name> folder of host to the /mnt folder of the existing (not running) container.

1. stop docker container or whole docker engine

```
systemctl stop docker.service
```

2. Open configuration file corresponding to the stopped container, which can be found at /var/lib/docker/containers/99d...1fb/config.v2.json (may be config.json for older versions of docker). For pretty print use

```
vi <(jq . /var/lib/docker/containers/<container-ID>/config.v2.json)
Save updates to a file: :w config.v2.json
Exit vim: :q!
Update existing file: jq -c . config.v2.json >
/var/lib/docker/containers/<container-ID>/config.v2.json
```

3. Find MountPoints section: "MountPoints":{}
4. Replace the contents with something like this (you can copy proper contents from another container with proper settings):

```
"MountPoints":{"/mnt":{"Source":"/home/<user-
name>","Destination":"/mnt","RW":true,"Name":"","Driver":"","Type":"bin
```

```
d", "Propagation": "rprivate", "Spec": {"Type": "bind", "Source": "/home/<user-name>", "Target": "/mnt"}, "SkipMountpointCreation": false}}
```

or the same (formatted):

```
"MountPoints": {
  "/mnt": {
    "Source": "/home/<user-name>",
    "Destination": "/mnt",
    "RW": true,
    "Name": "",
    "Driver": "",
    "Type": "bind",
    "Propagation": "rprivate",
    "Spec": {
      "Type": "bind",
      "Source": "/home/<user-name>",
      "Target": "/mnt"
    },
    "SkipMountpointCreation": false
  }
}
```

5. Start or restart the docker service:

```
systemctl start docker.service
service docker restart
```

6. Start the container if necessary:

```
docker start <container-name/ID>
```

From:

<http://wuff.dyndns.org/> - **Wulf's Various Things**

Permanent link:

<http://wuff.dyndns.org/doku.php?id=linux:docker&rev=1685748042>

Last update: **2023/06/03 00:20**

